MPN: B-FTP605W

Patchcable, F/UTP (FTP), Cat6, 5.0m

CAT6 cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 250Mhz (CAT6 standard) and are backwards compatible with CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space. Furthermore this cable is manufactured with shielding. This protects against both EMI (electromagnetic interference). EMI can cause crosstalk between circuits, resulting in degradation of data, increased errors and slower transmission rates, but by using this shielded cable you will avoid this problem.

- F/UTP Shielding, protects again EMI (Electromagnetic interference)
- with Latch Protection
- with slimline strain relief, with gold plated PINs
- high and low interference protections
- mechanical durability for vibrations

Caractéristiques

Autres caractéristiques	**Caractéristiques**	Kink Protection, strain relief and Latch Protection
	Série de produit	Round Cable
Batterie	**Battery Type**	NONE - Only use for non-battery items
Caractéristiques	**Blindage du câble**	F/UTP (FTP)
	Câble standard	Cat6
	Conformité RoHS	Oui
	Connecteur 1	RJ45
	Connecteur 2	RJ45
	Couleur du produit	Blanc
	Fréquence	250 MHz
	Genre de connecteur 1	Mâle
	Genre de connecteur 2	Mâle
	Longueur de câble	5 m
	Matériau conducteur	Aluminium cuivré (CCA)
	Matériau du manteau	Polyvinyl chloride (PVC)
	Plug and Play	Oui
	Taille des fils AWG	26
	Taux de transfert de données	10000 Mbit/s
	Type de conducteur	Stranded
Informations sur l'emballage	**Quantité**	1 pièce(s)
Package dimensions (verified)	**Depth Verified**	14,9 cm
	Gross Weight Verified	0,144 kg

Package dimensions (verified)	**Height Verified**	3,8 cm
	Width Verified	15,6 cm
Poids et dimensions	**Diamètre extérieur**	5,6 mm
Product dimensions	**Net Weight (Product, kg)**	0,1 kg
Vendor information	**Brand Name**	MicroConnect
	Warranty	25 Année (s)

Autres produits de cette série

Longueur de câble	Blanc	Bleu	Gris	Jaune
0,25	B-FTP60025W	B-FTP60025B	B-FTP60025	B-FTP60025Y
0,5	B-FTP6005W	B-FTP6005B	B-FTP6005	B-FTP6005Y
1,0	B-FTP601W	B-FTP601B	B-FTP601	B-FTP601Y
1,5	B-FTP6015W	B-FTP6015B	B-FTP6015	B-FTP6015Y
2,0	B-FTP602W	B-FTP602B	B-FTP602	B-FTP602Y
3,0	B-FTP603W	B-FTP603B	B-FTP603	B-FTP603Y
5,0	B-FTP605W	B-FTP605B	B-FTP605	B-FTP605Y
7,5	B-FTP6075W	B-FTP6075B	B-FTP6075	B-FTP6075Y
10,0	B-FTP610W	B-FTP610B	B-FTP610	B-FTP610Y
15,0		B-FTP615B	B-FTP615	
20,0		B-FTP620B	B-FTP620	

Longueur de câble	Noir	Orange	Rose	Rouge
0,25	B-FTP60025S	B-FTP60025O	B-FTP60025PI	B-FTP60025R
0,5	B-FTP6005S	B-FTP6005O		B-FTP6005R
1,0	B-FTP601S	B-FTP601O		B-FTP601R
1,5	B-FTP6015S	B-FTP6015O	B-FTP6015PI	B-FTP6015R
2,0	B-FTP602S	B-FTP602O	B-FTP602PI	B-FTP602R-SOFTCAT
3,0	B-FTP603S	B-FTP603O	B-FTP603PI	B-FTP603R-SOFTCAT
5,0	B-FTP605S	B-FTP605O		B-FTP605R
7,5	B-FTP6075S	B-FTP6075O		B-FTP6075R
10,0	B-FTP610S	B-FTP610O		B-FTP610R
15,0	B-FTP615S			
20,0	B-FTP620S			

Longueur de câble	Vert	Violet
0,25	B-FTP60025G	B-FTP60025P
0,5	B-FTP6005G	B-FTP6005P
1,0	B-FTP601G	B-FTP601P
1,5	B-FTP6015G	B-FTP6015P
2,0	B-FTP602G	B-FTP602P
3,0	B-FTP603G	B-FTP603P

Longueur de câble	Vert	Violet
5,0	B-FTP605G	B-FTP605P
7,5	B-FTP6075G	B-FTP6075P
10,0	B-FTP610G	B-FTP610P
15,0	B-FTP615G	
20,0	B-FTP620G	